

linea m connection cable

Dimensions

Metric:
305 mm, 915 mm, 1525 mm, 3050 mm (X)
mm (Y)
mm (Z)
Imperial
12.01 in, 36.03 in, 60.04 in, 120.08 in (X)
0.00 Inch (Y)
0.00 Inch (Z)

Technical Data

Outer cable diameter	8 mm | 0.32 in
Outer diameter connector	35 mm | 1.38 in
Minimum bending radius Cable (fixed installation)	4x Outer Ø
Minimum bending radius cable (flexible)	15x Outer Ø
Environment	Indoor, Outdoor
Ingress protection rating	IP67
Ambient temperature (Operation)	-40 °C to 80 °C | -40 °F to 176 °F
Approbation	CE, ETL
	Designed and Developed in Bavaria. Made in Germany.

sales@biontechnologies.com
www.biontechnologies.com
Phone:
(DE) +49 8231 95787 0

All information without guarantee. Errors, changes and misprints excepted.

linea m connection cable

Configurator

LIN-M-CON -(1)-Y03

1 Dimension	
305	305 mm / 12.01 in
915	915 mm / 36.02 in
1525	1525 mm / 60.04 in
3050	3050 mm / 120.08 in

sales@biontechnologies.com
www.biontechnologies.com
Phone:
(DE) +49 8231 95787 0

All information without guarantee. Errors, changes and misprints excepted.