

linea m eco

Color Changing


The **linea m** combines modern design, high efficiency, and robust construction in a versatile linear lighting solution. With its premium build quality and reliable technology, it is suitable for both indoor and outdoor applications.

The **linea m** offers exceptional optical flexibility with four variants: **pureWhite**, **pureColor**, **tunableWhite**, and **RGBW**. While pureWhite provides natural illumination in different color temperatures, pureColor options create vivid accents in red, green, blue, and amber. The tunableWhite technology allows seamless adjustment of color temperature, while RGBW combines saturated colors with pure white for dynamic lighting effects.

Available in two performance classes – **eco** and **hp**, the eco variant is optimized for energy efficiency, making it ideal for applications with a strong focus on sustainability. The hp variant, on the other hand, delivers a higher light output for demanding lighting scenarios requiring maximum brightness. Both versions ensure excellent light quality and can be tailored to various application needs.

With a **wide range of beam angles** – from narrow to wide distributions – the linea m can be perfectly adapted to specific lighting requirements. Additionally, **optional anti-glare systems**, such as internal honeycomb grids or linear glare control, provide precise light control for enhanced visual comfort.

Dimensions



| | |
|----------------------------------|---------------|
| Metric: | |
| 629 mm, 934 mm, 1239 mm (X) | 75 mm (Y) |
| | 71 mm (Z) |
| Imperial | |
| 24.77 in, 36.78 in, 48.78 in (X) | 2.96 Inch (Y) |
| | 2.80 Inch (Z) |

Technical Data

| | | |
|--|---|---|
| Luminous color | RGBW2200K, RGBW2700K, RGBW3000K, RGBW4000K | 1239 mm 48.78 in → 9.0 kg 19.9 lb The weight of the fixture can vary depending on the configuration! |
| Luminous flux | 629 mm 24.77 in → max. 1116 lm 934 mm 36.78 in → max. 1674 lm 1239 mm 48.78 in → max. 2232 lm | |
| Number of LED(s) | 629 mm 24.77 in → 16 LEDs 934 mm 36.78 in → 24 LEDs 1239 mm 48.78 in → 32 LEDs | |
| Glare Protection | No Glare Protection, Honeycomb louver (internal, 6,4mm), Linear louver (internal) | |
| Dimming | Non dimmable Integrated interface(s) / control: NDIMtc, 0-10 V, DALI, DMX, IoT | |
| Housing | Extruded aluminium profile | |
| Housing color | Aluminium anodized, Black anodized | |
| Lens | Ultra clear, tempered safety glass | |
| Weight | 629 mm 24.77 in → 5.0 kg 11.1 lb 934 mm 36.78 in → 7.0 kg 15.5 lb | |
| Environment | | Indoor, Outdoor |
| Ingress protection rating | | IP66 |
| Humidity | | 0 to 95%, non-condensing |
| Ambient temperature (Operation) | | -40 °C to 40 °C -40 °F to 104 °F |
| Ambient temperature (Storage) | | -40 °C to 80 °C -40 °F to 176 °F |
| Ambient temperature (Start-up process) | | -25 °C to 40 °C -13 °F to 104 °F |
| Lumen Maintenance [L70] @ 25 °C | | 65,000 h |
| Lumen Maintenance [L70] @ 40 °C | | 40,000 h |
| Impact protection rating | | IK07 |

linea m eco *Color Changing*

Designed and Developed in Bavaria.
Made in Germany.

Electrical data

| | |
|---|---|
| Non dimmable | |
| Integrated interface(s) / control: NDIMtc, 0-10 V, DALI, DMX, IoT | |
| Internal power supply | 100 - 240, 277 VAC (50 - 60 Hz) |
| Power Consumption | 629 mm 24.77 in → 26 W 934 mm 36.78 in → 39 W 1239 mm 48.78 in → 42 W |
| Protection class | I |
| Inrush @ 230 V | 629 mm / 24.76 in → 50 A (Coldstart, $t_{width} = 210 \mu s$ measured at 50% I_{peak}) 934 mm / 36.77 in → 55 A (Coldstart, $t_{width} = 270 \mu s$ measured at 50% I_{peak}) 1239 mm / 48.78 in → 55 A (Coldstart, $t_{width} = 270 \mu s$ measured at 50% I_{peak}) |
| Power factor correction @ 230 V | 629 mm / 24.76 in → 0.95 934 mm / 36.77 in → 0.95 1239 mm / 48.78 in → 0.95 |
| LED-Class | Class 2 LED-Product |
| Approbation | CE, ETL, FCC |

Beam Angles

