

# linea xs eco
## Color Changing

The **linea xs** is an impressive low-voltage member of the **linea family** of linear façade luminaires. It not only offers the usual high lighting technology and versatility in beam angles but also expands these with additional options such as integrable linear louvers or honeycomb louvers, which enable optimal glare control.

The innovative **one-block design** ensures that the housing is made from a single piece, minimizing the number of sealing surfaces and thus reducing potential weak points in the construction.

The use of high-quality materials such as highly refined extruded aluminum profiles and low-iron, pre-stressed glass ensures a long lifespan for the luminaire, even under challenging conditions.

## Dimensions




**Metric:**
324 mm, 477 mm, 629 mm, 782 mm, 934 mm, 1087 mm, 1239 mm (X)
46 mm (Y)
57 mm (Z)
**Imperial**
12.76 in, 18.78 in, 24.77 in, 30.79 in, 36.78 in, 42.80 in, 48.78 in (X)
1.82 Inch (Y)
2.25 Inch (Z)

## Technical Data

| | |
|---|---|
| Luminous color | RGBA, RGBW2200K, RGBW2700K, RGBW3000K, RGBW4000K |
| Luminous flux | 324 mm \| 12.76 in → max. 558 lm<br>477 mm \| 18.78 in → max. 837 lm<br>629 mm \| 24.77 in → max. 1116 lm<br>782 mm \| 30.79 in → max. 1395 lm<br>934 mm \| 36.78 in → max. 1674 lm<br>1087 mm \| 42.80 in → max. 1953 lm<br>1239 mm \| 48.78 in → max. 2232 lm |
| Number of LED(s) | 324 mm \| 12.76 in → 8 LEDs<br>477 mm \| 18.78 in → 12 LEDs<br>629 mm \| 24.77 in → 16 LEDs<br>782 mm \| 30.79 in → 20 LEDs<br>934 mm \| 36.78 in → 24 LEDs<br>1087 mm \| 42.80 in → 28 LEDs<br>1239 mm \| 48.78 in → 32 LEDs |
| Glare Protection | No Glare Protection, Honeycomb louver (internal, 6,4mm), Linear louver (internal) |
| Dimming | Integrated interface(s) / control: DMX |
| Housing | Extruded aluminium profile |
| Housing color | Aluminium anodized, Black anodized |
| Lens | Ultra clear, tempered safety glass |
| Weight | 324 mm \| 12.76 in → 1.0 kg \| 2.3 lb<br>477 mm \| 18.78 in → 1.6 kg \| 3.6 lb<br>629 mm \| 24.77 in → 2.1 kg \| 4.7 lb<br>782 mm \| 30.79 in → 2.7 kg \| 6.0 lb<br>934 mm \| 36.78 in → 3.2 kg \| 7.1 lb<br>1087 mm \| 42.80 in → 3.8 kg \| 8.4 lb<br>1239 mm \| 48.78 in → 4.3 kg \| 9.5 lb<br>The weight of the fixture can vary depending on the configuration! |
| Environment | Indoor, Outdoor |
| Ingress protection rating | IP66 |
| Humidity | 0 to 95%, non-condensing |
| Ambient temperature (Operation) | -40 °C to 40 °C \| -40 °F to 104 °F |
| Ambient temperature (Storage) | -40 °C to 80 °C \| -40 °F to 176 °F |
| Ambient temperature (Start-up process) | -25 °C to 40 °C \| -13 °F to 104 °F |
| Lumen Maintenance [L70] @ 25 °C | 65,000 h |
| Lumen Maintenance [L70] @ 40 °C | 40,000 h |
| Impact protection rating | IK08 |
| Electrical data | |
| Integrated interface(s) / control: DMX | |
| Constant voltage | 36 V |
| Power Consumption | |

sales@biontechnologies.com
www.biontechnologies.com
Phone:
(DE) +49 8231 95787 0





All information without guarantee. Errors, changes and misprints excepted.


# linea xs eco *Color Changing*


| | |
|---|---|
| | 324 mm \| 12.76 in → 5 W<br>477 mm \| 18.78 in → 7 W<br>629 mm \| 24.77 in → 10 W<br>782 mm \| 30.79 in → 12 W<br>934 mm \| 36.78 in → 15 W<br>1087 mm \| 42.80 in → 17 W<br>1239 mm \| 48.78 in → 20 W |
| Protection class | III |
| LED-Class | Class 2 LED-Product |
| Approbation | CE, ETL, FCC |
| | Designed and Developed in Bavaria.<br>Made in Germany. |


## Beam Angles





















## Accessories



**linea xs / xc leader cable**



**linea xs/xc jumper cable**



**Switching Power Supply ND Series**



All information without guarantee. Errors, changes and misprints excepted.

BION TECHNOLOGIES

**linea xs eco** *Color Changing*

## Configurator

LIN-XS-ECO - (1) _____ - (2) _____ - (3) _____ - (4) _____ - (5) _____ - (6) _____ - (7) _____ - (8) _____ - (9) _____ - (10) _____ -Y01

| 1 Luminous color | |
|---|---|
| RGBA | RGBA |
| RGBW8322 | RGBW 2200 K (CRI > 80 / 3 SDCM) |
| RGBW8327 | RGBW 2700 K (CRI > 80 / 3 SDCM) |
| RGBW8330 | RGBW 3000 K (CRI > 80 / 3 SDCM) |
| RGBW8340 | RGBW 4000 K (CRI > 80 / 3 SDCM) |

| 2 Dimming | |
|---|---|
| DMX | DMX |

| 3 Dimension | |
|---|---|
| 324 | 324 mm / 12.76 in |
| 477 | 477 mm / 18.78 in |
| 629 | 629 mm / 24.76 in |
| 782 | 782 mm / 30.79 in |
| 934 | 934 mm / 36.77 in |
| 1087 | 1087 mm / 42.80 in |
| 1239 | 1239 mm / 48.78 in |

| 4 Beam Angle | |
|---|---|
| 8X8 | 8° x 8° |
| 10X10 | 10° x 10° |
| 23X23 | 23° x 23° |
| 43X43 | 43° x 43° |
| 8X31 | 8° x 31° |
| 10X42 | 10° x 42° |
| 12X60 | 12° x 60° |
| 14X100 | 14° x 100° |
| 30X60 | 30° x 60° |
| 60X30 | 60° x 30° |

| 5 Housing color | |
|---|---|
| AA | Aluminium anodized |
| BA | Black anodized |

| 6 Glare Protection | |
|---|---|
| OP | No Glare Protection |
| HL64 | Honeycomb louver (internal, 6,4mm) |
| LL0 | Linear louver (internal) |

| 7 Approbation | |
|---|---|
| CE | European Union |
| ETL | North America |

| 8 Wiring configuration | |
|---|---|
| IOCC | IN/OUT with Connector |
| IXCX | only IN with Connector |
| IOOO | IN/OUT with open ends |
| IOOC | IN open end / OUT socket |
| IXOX | only IN with open ends |

| 9 Leader cable length | |
|---|---|
| ETE | End to end - Leader length |
| 003 | 30 cm (11.8 in) leader cable |
| 006 | 60 cm (23.6 in) leader cable |
| 009 | 90 cm (35.4 in) leader cable |
| 012 | 1,2 m (47.2 in) leader cable |
| 015 | 1,5 m (59 in) leader cable |

sales@biontechnologies.com
www.biontechnologies.com
Phone:
(DE) +49 8231 95787 0



All information without guarantee. Errors, changes and misprints excepted.

# linea xs eco *Color Changing*

| 10 Mounting | |
|---|---|
| BS | Universal mounting bracket |
| BSB | Universal mounting bracket burnished |
| FX015 | Fix 0° -15°, SW 5° |
| ND | without bracket |

sales@biontechnologies.com
www.biontechnologies.com
Phone:
(DE) +49 8231 95787 0



All information without guarantee. Errors, changes and misprints excepted.