




murus m

Color Changing

Dimensions



Metric:
130 x 150 x 170 mm [X x Y x Z]
Imperial
5.12 x 5.91 x 6.70 in [X x Y x Z]


Technical Data

Luminous color	RGBW3000K, RGBW4000K
Luminous flux	max. 600 lm
Number of LED(s)	1 LED
Glare Protection	Honeycomb louver (internal, 6,4mm), Linear louver 0° (internal)
Dimming	Integrated interface(s) / control: DMX, IoT
Housing	Aluminium die casting
Housing color	DB 703 metallic dark grey fine-textured, RAL 9003 Signal white fine-textured matt, RAL 9005 Jet black, fine-textured matt, RAL_____(fine-textured, matt), RAL_____, (smooth, matt)
Lens	Ultra clear, tempered safety glass
Environment	Indoor, Outdoor
Ingress protection rating	IP66
Humidity	0 to 95%, non-condensing
Ambient temperature (Operation)	-40 °C to 40 °C -40 °F to 104 °F
Ambient temperature (Storage)	-40 °C to 80 °C -40 °F to 176 °F
Ambient temperature (Start-up process)	-25 °C to 40 °C -13 °F to 104 °F
Lumen Maintenance [L70] @ 25 °C	65,000 h
Lumen Maintenance [L70] @ 40 °C	40,000 h

Impact protection rating	IK08
Electrical data	Integrated interface(s) / control: DMX, IoT
Internal power supply	100 - 240, 277 VAC (50 - 60 Hz) 127 - 431 VDC
Protection class	I
LED-Class	Class 2 LED-Product
Approbation	CE

Designed and Developed in Bavaria.
Made in Germany.

Beam Angles



Configurator



Product Code: MUR-M - _ - _ - _ - _ - _ - _ -Y01

1 Housing design	
SC	Snoot 360°
SF	Snoot front
SL	Snoot Left
SR	Snoot Right
SX	No snoot

2 Luminous color	
RGBW83 30	RGBW3000 K / 3 SDCM / CRI > 80
RGBW83 40	RGBW4000 K / 3 SDCM / CRI > 80

3 Dimming	
DMX	DMX
IOT	IoT

4 Approbation	
CE	European Union

5 Beam Angle	
10X10	10° x 10°
22X22	22° x 22°
34X34	34° x 34°
60X60	60° x 60°
8X31	8° x 31°
10X40	10° x 40°
12X60	12° x 60°
14X100	14° x 100°
30X60	30° x 60°
30X58Y -14L	30° x 58° y -14° L
30X11Y -14R	30° x 11° y -14° R

6 Glare Protection	
OP	No Glare Protection
HL64	Honeycomb louver (internal, 6,4mm)
LL00	Linear louver 0° (internal)

7 Housing color	
DB703	DB 703 metallic dark grey fine-textured
R9003F M	RAL 9003 Signal white fine-textured matt
R9005F M	RAL 9005 Jet black, fine- textured matt
R____F M	RAL____,(fine-textured, matt)
R____S M	RAL____, (smooth, matt)