




murus m

Color Changing

Dimensions



Metric:

130 x 150 x 170 mm [X x Y x Z]

Imperial

5.12 x 5.91 x 6.70 in [X x Y x Z]

Technical Data

Luminous color	RGBW3000K, RGBW4000K
Luminous flux	max. 600 lm
Number of LED(s)	1 LED
Glare Protection	Honeycomb louver (internal, 6,4mm), Linear louver 0° (internal)
Dimming	Integrated interface(s) / control: DMX, IoT
Housing	Aluminium die casting
Housing color	DB 703 metallic dark grey fine-textured, RAL 9003 Signal white fine-textured matt, RAL 9005 Jet black, fine-textured matt, RAL_____(fine-textured, matt), RAL_____, (smooth, matt)
Lens	Ultra clear, tempered safety glass
Environment	Indoor, Outdoor
Ingress protection rating	IP66
Humidity	0 to 95%, non-condensing
Ambient temperature (Operation)	-40 °C to 40 °C -40 °F to 104 °F
Ambient temperature (Storage)	-40 °C to 80 °C -40 °F to 176 °F
Ambient temperature (Start-up process)	-25 °C to 40 °C -13 °F to 104 °F
Lumen Maintenance [L70] @ 25 °C	65,000 h
Lumen Maintenance [L70] @ 40 °C	40,000 h
Impact protection rating	IK08

Electrical data

Integrated interface(s) / control: DMX, IoT	
Internal power supply	100 - 240, 277 VAC (50 - 60 Hz)
Protection class	I
LED-Class	Class 2 LED-Product
Approbation	CE

Designed and Developed in Bavaria.
Made in Germany.

Beam Angles

