



The recessed floor housing, made of high-quality aluminum extrusion profile (EN AW 6060), features an anodized finish and offers a durable solution for indoor and outdoor use. Specifically designed for the **tellus m** and **tellus point** recessed floor lights, it allows for flexible installation in various lengths – perfect for any project.

tellus m installation housing

Dimensions



Metric:

115 mm, 225 mm, 273 mm, 350 mm, 655 mm, 960 mm,

1265 mm (X)

114 mm (Y)

170 mm (Z)

Imperial 4.53 in, 8.86 in, 10.75 in, 13.78 in, 25.79 in, 37.80 in,

49.81 in (X)

4.49 Inch (Y)

6.70 Inch (Z)

Technical Data

recilifical Date	u
Material	Aluminum extruded profile (EN AW
Accessories	6060)
Housing Color	Aluminium anodized
Load	500 kg 1103 lb ₁
Environment	Gel-filled cable jointdoor, Outdoor
Approbation	CE, ETL
Wei	350 mm 13.78 in -> 2.1 kg 4.7 lb
	655 mm 25.79 in -> 3.8 kg 8.4 lb
	960 mm 37.80 in -> 5.5 kg 12.2 lb
	1265 mm 49.81 in -> 7.2 kg 15.9 lb
	The weight of the fixture can vary
	depending on the configuration!
	Designed and Developed in Bavaria.

Made in Germany.





tellus m installation housing

Configurator

Product Code: TEL-M-INBX - ____-Y02

1 Dimension	
115	115 mm / 4.53 in
225	225 mm / 8.86 in
273	273 mm / 10.75 in
350	350 mm / 13.78 in
655	655 mm / 25.79 in
960	960 mm / 37.80 in
1265	1265 mm / 49.80 in