



The recessed floor housing, made of high-quality aluminum extrusion profile (EN AW 6060), features an anodized finish and offers a durable solution for indoor and outdoor use. Specifically designed for the **tellus m** and **tellus point** recessed floor lights, it allows for flexible installation in various lengths – perfect for any project.

tellus m installation housing

Dimensions



Metric:

115 mm, 225 mm, 273 mm, 350 mm, 655 mm, 960 mm,

1265 mm (X)

114 mm (Y)

170 mm (Z) Imperial

4.53 in, 8.86 in, 10.75 in, 13.78 in, 25.79 in, 37.80 in,

49.81 in (X)

4.49 Inch (Y)

6.70 Inch (Z)

Technical Data

| Material | Aluminum extruded profile (EN AW |
|---------------|----------------------------------|
| | 6060) |
| Housing Color | Aluminium anodized |
| Environment | Indoor, Outdoor |
| Approbation | CE, ETL |

Designed and Developed in Bavaria.

Made in Germany.





Accessories









tellus m installation housing

Configurator

Product Code: TEL-M-INBX -____-Y02

| 1 Dimension | |
|-------------|--------------------|
| 115 | 115 mm / 4.53 in |
| 225 | 225 mm / 8.86 in |
| 273 | 273 mm / 10.75 in |
| 350 | 350 mm / 13.78 in |
| 655 | 655 mm / 25.79 in |
| 960 | 960 mm / 37.80 in |
| 1265 | 1265 mm / 49.80 in |