




# VS-Series 100

The **VS-Series** is a universal power supply designed for **tantulus** lighting systems. It offers easy installation, effortless commissioning, and long-term reliability. It is engineered for easy maintenance and provides a future-proof power solution you can count on.

## Dimensions



**Metric:**  
350 x 320 x 90 mm [X x Y x Z]  
**Imperial**  
13.78 x 12.60 x 3.55 in [X x Y x Z]

## Technical Data

Dimming Integrated interface(s) / control: 0-10 V, DALI, DMX, IoT

### Electrical data

Constant voltage	36 V
Protocol(s)	0-10 V, DALI, DMX, IoT
Input voltage	100 - 240, 277 VAC (50 - 60 Hz)
Protection class	I
Inrush @ 230 V	70 A
	(Coldstart, $t_{\text{Width}} = 1000 \mu\text{s}$ measured at 50% $I_{\text{peak}}$ )
Power factor correction @ 230 V	> 0.95 @ max. Output
Housing	Sheet steel
Housing Color	RAL 9010 pure white smooth satin finish
Environment	Indoor
Ingress protection rating	IP20
Ambient temperature (Operation)	-20 °C to 40 °C   -4 °F to 104 °F
Approbation	CE, ETL, FCC
Weight	5.7 kg

Designed and Developed in Bavaria.  
Made in Germany.

## Configurator



VS-100 - - - -Y02

1 Output	
36V	36V

2 Dimming	
010V	0-10 V
DALI	DALI
DMX	DMX
IOT	IoT

3 Approbation	
CE	European Union
ETL	North America

4 Application	
PWHP	pureWhite - hp/hpx
TW	tunableWhite
RGBW	RGBW